

# Natural Wood Cleaner

Flügger Natural Wood products are intended for the care and maintenance of indoor natural wood. Revitalises and protects while maintaining the structure of the wood and keeping the grain visible.

## Properties

Cleaning agent for natural wood. Removes grease, soap, wax and dirt before further treatment and maintenance.

- **Removes grease, soap, wax and dirt**
- **Prepare the surface effectively before treatment**
- **For use in interiors**



## Use

Cleaning of untreated, lye-treated, soap-treated oiled or varnished surfaces such as furniture, countertops and floors. For all types of wood before treatment with lye, soap, oil or varnish.

## Substrate

Must be clean, dry, firm and suitable for surface treatment.  
The surface must be able to withstand water and alkalines, pH 10.5.

## Treatment

Mix 1 part Flügger Natural Wood Cleaner with 20 parts warm water, but for varnished surfaces 1 part to 40 parts water. Wash the surface and let the mixture work for 5 minutes before wiping off with clean water. Repeat the treatment if the surface is extremely dirty.  
The surface must be completely dry before subsequent treatment.

## Application

Mop, floor scrub or cloth.  
Always wash along the length of the wood.  
Treat cleaned surfaces with lye, soap, oil or varnish.

## Expected result

Uniformly cleaned surface free of grease, soap, wax and dirt.

## Please note!

Flügger Natural Wood Cleaner can etch glass and attack metals.  
So make sure to cover surroundings to protect against splashing.

# Environmental information

Storage of unopened/opened packages: Cool, frost-free, and tightly closed.

Protective equipment for: Spray painting: Overalls, full-face mask with combined filter. Brush/roller application: Safety goggles and gloves. Sanding: Respiratory protection.

Environmental information: Remove as much paint as possible from brushes before washing them in water. Do not pour residue/remains of paint down the drain, take it to your local recycling centre. Minimise your paint waste by calculating how much paint you need in advance. Store leftover paint properly so the remains can be reused, which minimises the environmental impact.

**Storage:** Cool, frost free and tightly closed

## Technical Data

Product Type	Cleaning
Density (kgs/l)	1.04
pH	10.5
Mixture proportion	varnished wood floor: 1 part to 40 parts water  Oiled wood floor: 1 part to 20 parts water  Untreated or soap-treated wood floor: 1 part to 20 parts water
Nominal spreading rate (m <sup>2</sup> /ltr.)	250
Long spreading rate (m <sup>2</sup> /l)	300
Short Spreading rate (m <sup>2</sup> /l)	200
Min. working temp. during application and drying/curing	Min. +15°C
Drying time at 20° C, 60 % RH (Hours)	4
Recoatable at 20° C, 60 % RH (Hours)	8

### Current TDS Version

July 2022

### Replaces TDS Version

January 2019